





Table Top

Touch Screen Auto Ignition

Microprocessor based Flame Photometer Comprising of Aspirator Unit and Burner Unit.

User friendly, Menu driven with Printer Interface.

Can simultaneously analyze Na, K, Li, Ca and Ba in single aspiration of the sample with proper removal of interferences.

The instrument carries advanced features like automatic ignition, automatic gas shut off in case of power failure.

Calibration data saving & retrieval.

More than 800 samples saving facility.

SALIENT FEATURES

- Calibration curve programmability can be done using a maximum of 20 standards in the range of interest of the user, data processing through optional curve fitting techniques like segmental and quadratic.
- Analysis made much more simpler because of the multiple calibration curves saving facility.
- Optional PC compatibility with USB Interface.
- Saving Data and Retrieval of Standards & Samples.

Flame Photometer



APPLICATIONS

Determination of

- In Bio-Medical Investigations: Na & K in body fluids, Na, K and Li electrolytes in Serum. Ba in Fecal matter (from Barium meal, Barium swallow etc.).
- In Pharamaceuticals : Na, K, Ca nutrient solutions for cultivation of Antibiotics.
- In Pollution Monitoring & Control : Na, K & Ca in Natural, Spring, River, Sea boiler feed, Rings and Waste Water.
- In Food and Agriculture : Na & K content in Soils, Plant materials, Food & Beveranges, Ca in Wine.
- In Research Laboratories and Industries : Alkali metal in Pastes, Soda Glass, Ceramic and Chemical Industries, Na, K and Ca in Cement and its raw materials.
- Measurement of Alkali & Alkaline earth metals.



SPECIFICATIONS

SENSITIVITY			RANGE					FLAME SYSTEM	
Sodium (Na)		0.5 ppm	Sodium (Na)	0-1	IOO ppm	0-200 mE	q		
Potassium (K)		0.5 ppm	Potassium (K)	0-1	IOO ppm	0-100 mE	q	LPG & Oil free dry air	
Lithium (Li)		0.5 ppm	Lithium (Li)	0-1	IOO ppm	0-10 mEq			
Calcium (Ca)		15 ppm	Calcium (Ca)	15	-100 ppm	0-5 mEq		DETECTOR	
Barium (Ba)		50 ppm	Barium (Ba)	50	50-1000 ppm			DETECTOR	
			mEq values are clai	med with appropriate dilution				Silicon Photodiode	
LINEARITY / ACCURACY / REPRODUCIBILITY			REPEATABILITY						
Sodium (Na)		Less than 2%	Sodium (Na)	Better than 1% CV for 20 consecutive samples.					
Potassium (K)			Potassium (K)						
Lithium (Li)			Lithium (Li)						
Calcium (Ca)			Calcium (Ca)	3% CV for 20 consecutive samples of Concentrations between 50 to 199 ppm.					
Barium (Ba)			Barium (Ba)						
ASPIRATION		3 to 6 ml/min			DATA PRESENTATION				
ACCESSORIES SUPPLIED					Display 7" TFT Touch		Touch (h Color Graphical	
		Filters for Na, K, Oil free Air compressor with built-in air regulator, air filter and buffer tank,			POWER REQUIREMENT				
	5 c	5 cc beakers, Cleaning wire and Capillary.			90-260 V AC, 47-63 Hz, 1φ, 65 VA Max.				
At extra Cost		ers for Ca, Li & Ba, P tware.	rinter, PC and PC		PHYSICAL DIMENSIONS				
					Size (WxDxH	l) in mm	345	x 315 x 255	
					Weight (in k		Appr	ox. 10	



B-90, A.P.I.E., Sanathnagar, Hyderabad 500 018, Telangana., India Tel +91 40 44451234 Fax +91 40 23771639 info@elico.co

www.elico.co

Celebrating 60 years of our Journey

www.elico.co/60years

Ahmedabad ahm@elico.co +91 98241 75321

blr@elico.co +91 99000 28741

Bengaluru

Bhopal bpl@elico.co +91 99930 96876

Bhubaneswar bbr@elico.co +91 99371 12105

Chennai chn@elico.co +91 98402 65797 Cochin kel@elico.co +91 81291 84400

Delhi del@elico.co +91 98710 06104

Guwahati gau@elico.co +91 91211 77451

Hyderabad hyd@elico.co

© 2021 ELICO

+91 99896 25457

Kolkata kol@elico.co +91 91211 77452

Lucknow lku@elico.co +91 91980 01666 Mumbai mum@elico.co +91 77100 96111

Patna pat@elico.co +91 91211 77450

Visakhapatnam vtz@elico.co +91 99899 94532