


**SL 168**

PRODUCT SPECIFICATION SHEET

# Atomic Absorption Spectrophotometer





Burner Alignment



LCD Display



Ignition



PC

Two Hollow Cathode Lamps with independent Power Supply.

Self Diagnosis, Automatic Wavelength Selection and Auto scan for Peak Searching.

Automatic Setting of Parameters by selecting the Element.

### SALIENT FEATURES

- Microprocessor based, user friendly, Menu driven with printer interface and optional PC attachment through RS232C interface.
- Narrow Beam Optics fully sealed and Quartz over coated mirrors.
- Modes of operation include Absorbance, Emission and Concentration.
- Auto saving of all parameters & Auto-Bandwidth Selection.
- Integral Gas Control System with panel Flow Meters.
- Precise Knobs for Vertical, Horizontal and Rotational alignment of Titanium Burner.
- The Software has facilities to repeat the result of the sample and data treatment.
- Automatic calculation of percentage and ppm in base material.
- Absorbance Mode has the facility to measure sample absorbance for selected number of points and to calculate Mean, SD and RSD.
- Optional PC Compatibility.

- Microsoft Windows® based software for Data processing, Storage, Retrieval, Interpretation etc.
- **OPTIONAL** : Hydride Generator

### SOFTWARE FEATURES

- **Microsoft Windows® based PC operating Software.**
- Easy User Interface.
- Linear / Quadratic curve equation to predict the sample concentrations.
- Modes of operation include Absorbance, Emission, Concentration and Standard Addition.
- Saving facility for the scanned Data.
- Print facility for all the scanned Data in Graph and Tabular formats.
- Software is 21 CFR Part 11 compliant with password method protection, Instrument logbook etc.




2 line Display



Gas Box



Burner Assembly with Air - Acetylene Flame




Burner Assembly with Nitrous - Acetylene Flame



Lamp Holder

## Attachments



Hydride Generator

## APPLICATIONS

In the fields of



## Soil Testing



MicroNutrients



Agriculture



Metals



Water



Mines & Geology



Fertilizer



Environmental & Pollution



Food & Beverages



Oil & Gas



Pharmaceutical



Coal



Glass



Cement



Research



Pesticide

# SPECIFICATIONS

## SPECTRAL

Range	185 to 900 nm
Bandwidth	Automatic variable slit from 0.15 to 3.0 nm continuously variable with increment of 0.15 nm
Readability	0.1nm
Accuracy	± 0.5 nm
Repeatability	± 0.2 nm

## DETECTOR

Photo Multiplier Tube (PMT)

## POWER SUPPLY

HC Lamp	0 to 30 mA modulated
PMT	-200 to -1000 Volts

## DATA PRESENTATION

Display	2 Line 24 Characters Dot Matrix Backlit LCD module
Hard Copy	On printer ( Centronics )

## FLOW CONTROL

Integral Gas Control System with Panel Flow Meters

<b>FUEL</b>	Acetylene (C <sub>2</sub> H <sub>2</sub> )
-------------	--

<b>OXIDANT</b>	Air / Nitrous Oxide (N <sub>2</sub> O)
----------------	--

## PHOTOMETRIC

Range	0 to 2 Abs
Accuracy	± 0.010 Abs at 1.0 Abs
Integration Time	0.04 to 99 sec

## LIGHT SOURCE

Hollow Cathode Lamps (HCL)

## MONOCHROMATOR

Czerney Turner 300 mm with 1200 lines/mm Holographic Diffraction Grating of High Density Hard Coded Optics

## DATA PROCESSING

Microprocessor Mode	1. Absorbance 2. Emission 3. Quantitative Curve fit (Linear and Quadratic)
PC Mode	Microsoft Windows® based PC Operating Software with following Operations  1. Absorbance 2. Concentration ( Standard Calibration and Addition), Curve fit Options Linear and Quadratic 3. Emission

## BURNER

Titanium construction, Premix, Laminar Flow 100mm burner for Air - Acetylene (C<sub>2</sub>H<sub>2</sub>).

Optional - 50 mm burner for Nitrous Oxide (N<sub>2</sub>O)- Acetylene (C<sub>2</sub>H<sub>2</sub>).

The Spray Chamber is made of Inert Material fitted with adjustable impact bead Aerosol.

## NEUBULIZER

Made of fully Inert Material with 90% Platinum and 10% Iridium Alloy Capillary

**SAMPLE FEED RATE** 3 to 8 ml/min (Adjustable)

## PHYSICAL DIMENSIONS

**Size ( WxDxH) in mm** 700 x 490 x 330

**Weight (in kg)** Approx. 50

## SYSTEM UPGRADATION

Instrument can be upgraded to Hydride and Cold vapour Generator

## POWER REQUIREMENT

230 V  $\pm$  10% AC, 50 Hz, 1 $\phi$ , 200 VA Max.

## ACCESSORIES SUPPLIED


**With Instrument** 100 mm burner for Air - C<sub>2</sub>H<sub>2</sub>, Nebulizer with SS Capillary, Oil free Air Compressor with 100% Dustfree Air Filter, Acetylene (C<sub>2</sub>H<sub>2</sub>) Regulator with Flashback Arrester.

**At extra Cost** 50 mm burner for N<sub>2</sub>O - C<sub>2</sub>H<sub>2</sub>, Nebulizer with Pt - Ir Capillary, N<sub>2</sub>O Regulator, Nitrogen Regulator, HC Lamps for desired Elements, Hydride and Cold vapour Generator, Printer, PC Software, Computer, Exhaust Fumehood Chamber, Servo Controlled Voltage Stabilizer of suitable rating, Acetylene Gas Cylinder, Nitrous Oxide Gas Cylinder and Nitrogen Gas Cylinder.

## ACCESSORIES



Air Compressor



Acetylene Regulator



Nebulizer



Nitrous Oxide Regulator



Air-Acetylene Flame Burner



HC Lamp (uncoded)



Nitrous-Acetylene Flame Burner

Celebrating 60 years  
of our Journey



[www.elico.co/60years](http://www.elico.co/60years)



[www.elico.co](http://www.elico.co)

**ELICO**®

An ISO 9001:2018 | 14001 | 27001 Certified Company

B-90, A.P.I.E., Sanathnagar, Hyderabad 500 018, Telangana., India

Tel +91 40 44451234 Fax +91 40 23771639 [info@elico.co](mailto:info@elico.co)

**Ahmedabad**

[ahm@elico.co](mailto:ahm@elico.co)  
+91 98241 75321

**Bengaluru**

[blr@elico.co](mailto:blr@elico.co)  
+91 99000 28741

**Bhopal**

[bpl@elico.co](mailto:bpl@elico.co)  
+91 99930 96876

**Bhubaneswar**

[bbr@elico.co](mailto:bbr@elico.co)  
+91 99371 12105

**Chennai**

[chn@elico.co](mailto:chn@elico.co)  
+91 98402 65797

**Cochin**

[kel@elico.co](mailto:kel@elico.co)  
+91 81291 84400

**Delhi**

[del@elico.co](mailto:del@elico.co)  
+91 98710 06104

**Guwahati**

[gau@elico.co](mailto:gau@elico.co)  
+91 91211 77451

**Hyderabad**

[hyd@elico.co](mailto:hyd@elico.co)  
+91 99896 25457

**Kolkata**

[kol@elico.co](mailto:kol@elico.co)  
+91 91211 77452

**Lucknow**

[lku@elico.co](mailto:lku@elico.co)  
+91 91980 01666

**Mumbai**

[mum@elico.co](mailto:mum@elico.co)  
+91 77100 96111

**Patna**

[pat@elico.co](mailto:pat@elico.co)  
+91 91211 77450

**Visakhapatnam**

[vtz@elico.co](mailto:vtz@elico.co)  
+91 99899 94532

